

CHAMPION AUTOLIFT TWO POST SPECIFICATION SHEET

MODEL	TP10F- HD	TP9 - HD	TP10A - HD	TP-11A-HD	TP12 - HD	TP12 - HD - XT
Capacity (LBS)	10,000	9,500	10,000	11,000	12,000	12,000
Overall Height	113"	141-1/2"	141-1/2"	149"	145-1/2"	165-1/2"
Overall Width	134-5/8"	134-5/8"	134-5/8"	137-5/8"	140"	140"
Width Between Post	109-1/2"	109-1/2"	109-1/2"	113-1/2"	116"	116"
Drive Thru Clearance	98"	98"	98"	103"	104"	104"
Voltage / Amps	220V / 30 A	220V / 30 A	220V / 30 A	220V / 30 A	220V / 30 A	220V / 30 A
Lift Travel	72"	72"	72"	72"	72"	72"
Low Pad Height	4-1/2"	4-1/2"	4-1/2"	4-1/2"	5"	5"
Pad at Full Rise	76-1/2"	76-1/2"	76-1/2"	76-1/2"	77"	77"
Adaptor	Stack	Stack	Stack	Threaded Stack	Stack	Stack
Minimum Concrete (Wire or Fiber Reinforced)	4" - 3500 PSI	4" - 3500 PSI	4" - 3500 PSI	4" - 3500 PSI	6" - 3500 PSI	6" - 3500 PSI

Specifications subject to change without notice



CHAMPION
AUTOLIFT.COM

1.800.844.9608
@championautolift